

CASEMENT WINDOWS



GLAZING SPECIFICATION

INTERNAL BEADED (REVERSE BUTT WELDED) 28MM

SPECIFICATION	STANDARD	ALTERNATIVE
COLOUR	WHITE	ROSEWOOD OR CHERRYWOOD ON WHITE OR ROSEWOOD OR CHERRYWOOD ON BROWN
TRANSOM/MULLION JOINTS	WELDED	NONE
OUTER FRAME PROFILE	SLIMLINE 56MM	70MM OR ODD LEG 64MM
SASH PROFILE	75MM	NONE
TRANSOM / MULLION PROFILE	64MM	86MM
CILL COLOUR	WHITE	ROSEWOOD OR CHERRYWOOD ON WHITE OR ROSEWOOD OR CHERRYWOOD ON BROWN
CILL TYPE	155MM	85, 125, 185MM OR NONE
CILL HORNS	100MM	NO HORNS OR OVER 100MM (STATE LENGTH IF OVER)
FURNITURE COLOUR	WHITE WITH WHITE FRAMES WHITE WITH WOODGRAIN ON WHITE FRAMES GOLD WITH WOODGRAIN FRAMES	GOLD, SILVER GOLD, SILVER NONE
LOCK TYPE	MULTILOCK	MARINE MULTILOCK SHOOTBOLT MARINE SHOOTBOLT (S/S)
LOCK TYPE - FIRE ESCAPE WINDOW	MASTER - ESPAGNOLETTE SLAVE - SHOOTBOLT (HANDLE OP)	MARINE
TRICKLE VENT	NONE	3000, 4000 OR 6000SQ.MM IN 70MM OUTER, SASH OR 45MM EXT
REINFORCEMENT	TO BS7412	DETAILS ON REQUEST
GLAZING GASKET COLOUR	BLACK	NONE
HINGE TYPE	STANDARD FRICTION HINGE	EGRESS, RESTRICTOR, FIRE ESCAPE, SECURITY, MARINE PLUS OPTIONS
DRAINAGE	BOTTOM	FACE OR NONE
BEAD TYPE	28MM	NONE
GLASS UNIT SPACER	SILVER	WHITE, BLACK GOLD OR NO GLASS